



Design minimal
 Double aesthetic door
 Possible upwards smoke outlet

95% di efficiency
 Silent
 Wi-fi predisposition

Mod. 7/7C

180/200m³

Mod. 9/9C

220/240m³

Mod. 11/11C

270/290m³

TECHNICAL DATA		MOD 7	MOD 7C	MOD 9	MOD 9C	MOD 11	MOD 11C
Heat input (max - min)	kW	7,9 - 3,9	7,9 - 3,9	9,6 - 3,9	9,6 - 3,9	11,8 - 3,9	11,8 - 3,9
Nominal heat output (max - min)	kW	7,5 - 3,7	7,5 - 3,7	9,0 - 3,7	9,0 - 3,7	11 - 3,7	11 - 3,7
Pellet consumption (max - min)	Kg - h	1,65 - 0,8	1,65 - 0,8	1,99 - 0,8	1,99 - 0,8	1,65 - 0,8	1,65 - 0,8
Efficiency (max - min)	%	95 - 95	95 - 95	95 - 94,2	95 - 94,2	95 - 93	95 - 93
Smoke outlet tube	Ø mm	80	80	80	80	80	80
Tank capacity	lt - kg	16	16	16	16	16	16
Autonomy (max - min)	h	10 - 20	10 - 20	8 - 20	8 - 20	8 - 20	8 - 20
Nominal power input	W	40 - 300	86 - 300	48 - 300	94 - 300	58 - 300	104 - 300
Dimensions (W x D x H)	mm	475 x 490 x 940	475 x 490 x 940	475 x 490 x 940	475 x 490 x 940	475 x 490 x 100	475 x 490 x 100
Net weight	kg	100	100	100	100	110	110

All data and pictures are indicative and provisional and subject to change without notice. The value of the volume refers to isolated buildings and it's only indicative.